



Hangzhou Risingsun Cable Co., Ltd

Applications:

Low-power video and RF signal connections Indoor CATV, CCTV system
Siamese cables give you the power to centralize your video and power distribution for your CCTV systems, and allows for more flexible placement of your security cameras.

KX6+2C

CCTV CABLE

Construction:	Material	Diameter(mm)
Conductor	Bare Copper	7×0.2
Insulation	Solid Polyethylene	3.66
1 st Shield	78% Coverage CCA Braiding	/
Jacket	PVC	6.0
Power Wire Conductor	Stranded Bare Copper	2×16×0.20
Power Wire Insulation	PVC(Red/Black)	1.80
Jacket	PVC	9.5±0.3

Electrical Characteristics:

Capacitance(pF/m)	67±2
Impedance(Ω)	75±3
Velocity of Propagation(%)	66
Retrun Loss(dB)	≥20
Shielding Effectiveness(dB)	>80
Spark Test(VAC)	3000
Operating Temp Range(°C)	-20 to 70

Attenuation (20 °C)

Frequency(Mhz)	Max Attenuation(dB/100ft)	Max Attenuation(dB/100m)
10	1.5	5.0
50	2.5	8.1
100	4.0	13.0
200	5.6	18.5
400	6.9	22.5
800	10.5	34.5
950	11.5	37.5
1000	13.7	45.0

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698 Fax:86-571-63766808

Web:www.rscable.com