



Hangzhou Risingsun Cable Co., Ltd

Applications:

Low-power video and RF signal connections Indoor CATV, CCTV system
Siamese cables give you the power to centralize your video and power distribution for your CCTV systems, and allows for more flexible placement of your security cameras.

RG59+2C

SIAMESE CABLE

Construction:	Material	Diameter(mm)
Conductor	Bare Copper	0.81
Insulation	Foam Polyethylene	3.66
1 st Shield	Bonded Aluminum Foil	/
2 nd Shield	95% Coverage CCA Braiding	/
Jacket	PVC	6.1
Power Wire Conductor	Bare Copper	1.0
Power Wire Insulation	PE(Red/Black)	1.90
Jacket	PVC	5.30

Electrical Characteristics:

Capacitance(pF/m)	52±2
Impedance(Ω)	75±3
Velocity of Propagation(%)	85
Retrun Loss(dB)	≥20
Inner Conductor Resistance(Ω/km)	35.73
Spark Test(VAC)	3000
Operating Temp Range(°C)	-20 to 70

Attenuation (20 °C)

Frequency(Mhz)	Max Attenuation(dB/100ft)	Max Attenuation(dB/100m)
1	0.45	1.48
10	0.90	2.95
50	1.90	6.23
100	3.20	10.49
200	4.00	13.11
400	4.90	16.07
700	8.60	28.20
900	9.80	32.13
1000	10.70	35.08

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698 Fax:86-571-63766808

Web:www.rscable.com