



Hangzhou Risingsun Cable Co., Ltd



RSLMR195

Construction		Material	Diameter(inch/mm)	
Inner Conductor		Solid Bare Copper	0.037	0.94
Dielectric		Foamed PE	0.110	2.79
First Shield		Bonded Alumium Foil	0.116	2.95
Second Shield		90% Tinned Copper Braid	0.139	3.53
Jacket	Outdoor	PE	0.195	4.95
	Indoor	PVC/TPE	0.195	4.95

Electrical Characteristics

Capacitance(pF/m)	83.3
Impedance(Ω)	50
Velocity of Propagation(%)	75.0
Conductor DCR(Ohm/km)	24.9
Outer shleid DCR(Ohm/km)	16.1
Return Loss(dB)	≥ 20
Shielding Effectiveness(dB)	> 90
Max Operating Voltage(RMS)	3000
Operating Temp Range($^{\circ}\text{C}$)	-40 to 85

Attenuation (20 $^{\circ}\text{C}$)

Frequency(Mhz)	Max Attenuation(dB/100ft)	Max Attenuation(dB/100m)
30	2.0	6.5
50	2.5	8.4
150	4.4	14.6
220	5.4	17.7
450	7.8	25.5
900	11.1	36.5
1500	14.5	47.7
1800	16.0	52.5
2000	16.9	55.4
2500	19.0	62.4
5800	29.9	98.1

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698

Fax: 86-571-63766808

Web:www.rscable.com