



Hangzhou Risingsun Cable Co., Ltd

Applications:

Generally used for connecting alarm equipment such as sensors, control panels and other low voltage circuits.

Shielded Alarm Cable

No of Cores	Construction	Material	Diameter(mm)	
2C	Stranded Conductor	BC/ Tinned BC Tinned CCA/ CCA	7/0.254mm(22AWG)	7/0.20mm
	Dielectric	PVC	1.2mm	1.0mm
	1 st Shield	PET Mylar	/	/
	Drain Wire	BC/TC/TCCA/CCA	7/0.254mm	7/0.20mm
	2 nd Shield	Aluminum Foil	/	/
	Jacket	PVC/LSZH	4.0mm	3.6mm
4C	Stranded Conductor	BC/ Tinned BC Tinned CCA/ CCA	7/0.254mm(22AWG)	7/0.20mm
	Dielectric	PVC	1.2mm	1.0mm
	1 st Shield	PET Mylar	/	/
	Drain Wire	BC/TC/TCCA/CCA	7/0.254mm	7/0.20mm
	2 nd Shield	Aluminum Foil	/	/
	Jacket	PVC/LSZH	4.6mm	4.2mm
6C	Stranded Conductor	BC/ Tinned BC Tinned CCA/ CCA	7/0.254mm(22AWG)	7/0.20mm
	Dielectric	PVC	1.2mm	1.0mm
	1 st Shield	PET Mylar	/	/
	Drain Wire	BC/TC/TCCA/CCA	7/0.254mm	7/0.20mm
	2 nd Shield	Aluminum Foil	/	/
	Jacket	PVC/LSZH	5.5mm	4.6mm
8C	Stranded Conductor	BC/ Tinned BC Tinned CCA/ CCA	7/0.254mm(22AWG)	7/0.20mm
	Dielectric	PVC	1.2mm	1.0mm
	1 st Shield	PET Mylar	/	/
	Drain Wire	BC/TC/TCCA/CCA	7/0.254mm	7/0.20mm
	2 nd Shield	Aluminum Foil	/	/
	Jacket	PVC/LSZH	6.2mm	5.2mm

Remarks: OEM/ODM are welcomed

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698 Fax:86-571-63766808

Web:www.rscable.com