



Hangzhou Risingsun Cable Co., Ltd

Applications:

Wiring of fire alarms,Smoke detectors,Voice communications,Burglar Alarms
Fire protective circuits

Shielded Fire Alarm Cable

Construction:	Material
Conductor	Solid Bare Copper, Fully Annealed per ASTM B3
Insulation	Color-Coded, Polyvinylchloride (PVC)
Color-Code	Black/Red/Brown/Blue/Orange/Yellow/Violet/Gray
Shield	100% aluminum/polyester, 25% overlap Stranded tinned copper drain wire
Jacket	Red Polyvinylchloride (PVC)
Voltage Rating	300V
Temperature Range °C	-20 to 75

AWG Size	No of Cores	Insulation Dia(mm)	Jacket Dia(mm)
22	2	1.14	3.20
22	4	1.14	3.70
18	2	1.52	4.05
18	3	1.52	4.20
18	4	1.52	4.65
18	6	1.52	5.50
18	8	1.52	5.95
16	2	1.80	4.60
16	4	1.80	5.35
14	2	2.30	5.55
14	4	2.30	6.50

Packing Coil Packing/ Paper spool/ Pastic Spool/Wooden drum/

Remarks OEM/ODM are welcomed

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698 Fax:86-571-63766808

Web:www.rscable.com