




Hangzhou Risingsun Cable Co., Ltd

Multicore Overall Screened Cables-Belden Equivalent 8618

Applications:

These multicore overall screened cables have individually insulated cores laid up in an aluminum/polyester tape with a tinned copper drain wire. These cables are suitable for used as audio, control and instrumentation cables



Construction:

Conductor	Tinned Copper Wire
Insulation	PE
Overall Screen	Aluminum/Polyester tape
Drain Wire	Stranded Tinned Copper
Sheath	PVC(V Type)/LSZH(H type)
Insulation Colour	Black,Red,White

Electrical & Mechanical Characteristics:

AWG	16
Conductor Construction	19×0.287mm
UL Style	20253
Maximum Conductor Resistance (ohm/km)	15.8
Voltage Rating(V)	600
Nominal Capacitance Conductor to Conductor(pF/m)	85
Nominal Capacitance Conductor to Screen(pF/m)	164
Bending Radius	10×Overall Diameter
Operating Temperature(°C)	-20 to 60

Dimensions:

Ordering Code	No of Cores	Insulation Thickness (mm)	Sheath Thickness (mm)	Overall Diameter (mm)
RS8618V	3	0.79	0.79	8.3
RS8618H	3	0.79	0.79	8.3

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698 Fax:86-571-63766808

Web:www.rscable.com