




Hangzhou Risingsun Cable Co., Ltd

Multicore Overall Screened Cables-Belden Equivalent 9539

Applications:

These multicore overall screened cables have individually insulated cores laid up in an aluminum/polyester tape with a tinned copper drain wire. These cables are suitable for RS232 applications, used as audio, control and instrumentation cables.



Construction:

Conductor	Tinned Copper Wire
Insulation	PVC
Overall Screen	Aluminum/Polyester tape
Drain Wire	Stranded Tinned Copper 7×0.20mm
Sheath	PVC(V Type)/LSZH(H type)
Insulation Colour	Black,White,Red,Green,Brown,Blue,Orange,yellow,Purple

Electrical & Mechanical Characteristics:

AWG	24
Conductor Construction	7×0.20mm
UL Style	2464
Maximum Conductor Resistance (ohm/km)	85
Voltage Rating(V)	300
Nominal Capacitance Conductor to Conductor(pF/m)	98
Nominal Capacitance Conductor to Screen(pF/m)	180
Bending Radius	10×Overall Diameter
Operating Temperature(°C)	-30 to 80

Dimensions:

Ordering Code	No of Cores	Insulation Thickness (mm)	Sheath Thickness (mm)	Overall Diameter (mm)
RS9539V	9	0.25	0.81	6.2
RS9539H	9	0.25	0.81	6.2

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698 Fax:86-571-63766808

Web:www.rscable.com