



# Hangzhou Risingsun Cable Co., Ltd

**Item** 3C-2V With BNC Male to BNC Male Connector Extension Cable

## Description:

This high-quality cable is used widely in video and data applications including CCTV, broadcast, studio, home theater, etc.

The cable is often used as a generic carrier of signals in laboratories, BNC connectors are used on test and measurement equipment such as oscilloscopes, most two-way radio communication systems, CB radio, WLAN antennas, etc.

Heavy shielding protects the transmission data against electromagnetic interference (EMI) and radio frequency interference (RFI).

Accurately transfer high bandwidth frequency, jitter-free in video/data signals.

BNC connectors are used with miniature-to-subminiature coaxial cable in radio, television, and other radio-frequency electronic equipment, test instruments, and video signals.

## Specification:

Cable Type: 3C-2V Coaxial Cable

Material: Copper, PVC

Impedance: 75 Ohm

Rise time:  $\leq 3.5\text{ns}$

Storage Temperature:  $-20 \sim 75 \text{ }^\circ\text{C}$

Plug Type: BNC Male to BNC Male

Cable Diameter: 5.4mm / 0.21in

Maximum input current: 2.5A

Operating temperature:  $-10 \sim 50 \text{ }^\circ\text{C}$

Package Content: 1 x BNC Male to BNC Male Pigtail Cable



**Packing**

Slide Card Blister/Plastic Bag/Reel

**Remarks**

OEM/ODM are welcomed

**HANGZHOU RISINGSUN CABLE CO.,LTD**

Add: 1188 Jinxi Rd.s Linglong Industrial Zone Lin'an, Zhejiang, China

Tel: 86-571-63766698 Fax: 86-571-63766808

Web: [www.rscable.com](http://www.rscable.com)