




Hangzhou Risingsun Cable Co., Ltd

Multicore Overall Screened Cables-Belden Equivalent 8771

Applications:

These multicore overall screened cables have individually insulated cores laid up in an aluminum/polyester tape with a tinned copper drain wire. These cables are suitable for used as audio, control and instrumentation cables



Construction:

Conductor	Tinned Copper Wire
Insulation	PE
Overall Screen	Aluminum/Polyester tape
Drain Wire	Stranded Tinned Copper
Sheath	PVC(V Type)/LSZH(H type)
Insulation Colour	Black,Red,White

Electrical & Mechanical Characteristics:

AWG	22
Conductor Construction	7×0.254mm
UL Style	2093
Maximum Conductor Resistance (ohm/km)	54.8
Voltage Rating(V)	300
Nominal Capacitance Conductor to Conductor(pF/m)	75
Nominal Capacitance Conductor to Screen(pF/m)	135
Bending Radius	10×Overall Diameter
Operating Temperature(°C)	-20 to 60

Dimensions:

Ordering Code	No of Cores	Insulation Thickness (mm)	Sheath Thickness (mm)	Overall Diameter (mm)
RS8771V	3	0.41	0.84	5.1
RS8771H	3	0.41	0.84	5.1

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698 Fax:86-571-63766808

Web:www.rscable.com