



Hangzhou Risingsun Cable Co., Ltd

Applications:

BT3002-Multi8

boasts an impedance-matched design to ensure accurate digital signal handling. The quality metallic connectors provide maximum resistance for error-free data transfer, compatible with regular cable TV and TV antenna RF signals

With Braid Overall

Construction:	Material	Diameter(mm)
Conductor	Solid Bare Copper	0.31
Insulation	Solid Polyethylene	1.95
1 st Shield	91% Tinned Copper wire Braid	/
2 nd Shield	90% Tinned Copper wire Braid	/
Jacket	PVC	3.55±0.1
Shield	PET Tape	/
	Tinned Copper Wire Braid	
Jacket	PVC	14.8±0.5

Electrical Characteristics:

Capacitance(pF/m)	65±3
Impedance(Ω)	75±3
Velocity of Propagation(%)	67
DC Inner Conductor Resistance	≤235ohm/km
Operating Temp Range(°C)	-30 to 75

Attenuation (20 °C)

Frequency(Mhz)	Max Attenuation(dB/100ft)	Max Attenuation(dB/100m)
1	0.7	2.3
4	1.4	4.5
5	1.5	5.0
70	5.7	18.7

Remarks

OEM/ODM are welcomed

For more details of the cable,pls contact your sales representative

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698 Fax:86-571-63766808

Web:www.rscable.com