



Hangzhou Risingsun Cable Co., Ltd

Applications:

Designed to combine video, audio and communication systems with each other. They are used in TV transmission and TV camera csystem circuits.

CCTV4+1 Cable

Remove control is secured by connecting cameras located in the same system, monitors and mixers with each other.

Construction:		Material	Diameter(mm)
2Cores	Conductor	Bare Copper/CCA	7×0.18
	Insulation	PVC(Yellow/Green)	1.20
2Cores	Conductor	Bare Copper/CCA	16×0.18
	Insulation	PVC(Red/Black)	1.50
1 Coaxial Cable	Conductor	Bare Copper/CCA	7×0.16
	Insulation	Soild PE	2.60
	1 st Shield	Aluminum Foil	/
	2 nd Shield	Aluminum Wire/Tinned Copper Wire Braiding	3×16×0.12
5cores With Alunimum Polyester Tape			
CCTV4+1	Jacket	PVC	7.0±0.3

Electrical Characteristics:

Capacitance(pF/m)	67 ± 2
Impedance(Ω)	75±3
Rated voltage(V)	250
Test voltage(V)	1200
Operating Temp Range(°C)	-30 to 80

Attenuation (20 °C)

Frequency(Mhz)	Max Attenuation(dB/100m)
1	3.9
10	7.8
50	13.6
100	18.5
250	27.1

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698 Fax:86-571-63766808

Web:www.rscable.com