



Hangzhou Risingsun Cable Co., Ltd



P3 500M

Construction	Material	Diameter(mm)
Inner Conductor	Copper Clad Alumium	2.77
Dielectric	Foamed PE	11.43
First Shield	Seamless Aluminum tube(thickness)	0.61
Jacket	PE	14.22
Messenger	Galvanized Steel	2.77

Electrical Characteristics

Capacitance(pF/m)	50±3
Impedance(Ω)	75±3
Velocity of Propagation(%)	87
Retrun Loss(dB)	≥20
Shielding Effectiveness(dB)	≥100

Attenuation (20 °C)

Frequency(Mhz)	Max Attenuation(dB/100ft)	Max Attenuation(dB/100m)
5	0.16	0.52
55	0.54	1.77
83	0.66	2.17
211	1.09	3.58
250	1.20	3.94
300	1.31	4.30
350	1.43	4.69
400	1.53	5.02
500	1.73	5.68
600	1.91	6.27
750	2.16	7.09
865	2.34	7.68
1000	2.52	8.27

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698

Fax: 86-571-63766808

Web:www.rscable.com