



Hangzhou Risingsun Cable Co., Ltd



RG59 B/U-CCA

Construction	Material	Diameter(inch/mm)	
Inner Conductor	Bare Copper/CCS	0.023	0.58
Dielectric	Solid PE	0.146	3.70
First Shield	95% Copper Clad Aluminum Braid	/	/
Jacket	PVC	0.240	6.10

Electrical Characteristics

Capacitance(pF/m)	67±2
Impedance(Ω)	75±3
Velocity of Propagation(%)	66
Return Loss(dB)	≥20
Shielding Effectiveness(dB)	>75
Spark Test(VAC)	4000
Operating Temp Range(°C)	-40 to 85

Attenuation (20 °C)

Frequency(Mhz)	Max Attenuation(dB/100ft)	Max Attenuation(dB/100m)
10	1.2	4.1
50	2.9	9.5
100	3.7	12.1
200	5.6	18.4
400	7.6	25.0
600	9.8	32.2
860	11.5	37.6
1000	12.6	41.5

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698

Fax: 86-571-63766808

Web:www.rscable.com