



Hangzhou Risingsun Cable Co., Ltd

Description:

RG59B/U With Cat5e UTP

Make your cable installation easier with RisingSun's RG59 plus Cat5e Siamese Cable. It features 20 AWG coaxial cable together with 24 AWG Cat5e cable on an easy-pull spool

Siamese Cable

Construction:

RG59B/U+CAT5E UTP 24AWG

Electrical Characteristics:

Capacitance(pF/m)	67±2
Impedance(Ω)	75±3(RG59),100±15(CAT5E)
Velocity of Propagation(%)	66
Retrun Loss(dB)	≥20
Shielding Effectiveness(dB)	>75
Spark Test(VAC)	4000
Operating Temp Range(°C)	-40 to 85

Attenuation (20 °C)

Frequency(Mhz)	Max Attenuation(dB/100ft)	Max Attenuation(dB/100m)
10	1.2	4.1
50	2.9	9.5
100	3.7	12.1
200	5.6	18.4
400	7.6	25.0
600	9.8	32.2
860	11.5	37.6
1000	12.6	41.5

Frequency (MHz)	ATT (≤dB/100m)	NEXT (≥dB)	ELFEXT (≥dB)	RL (≥dB)	PS NEXT (≥dB)
1	2.0	65.3	63.8	20.0	62.3
4	4.1	56.3	51.7	23.0	53.3
8	5.8	51.8	45.7	24.5	48.8
10	6.5	50.3	43.8	25.0	47.3
16	8.2	47.3	39.7	25.0	44.3
20	9.3	45.8	37.7	25.0	42.8
25	10.4	44.3	35.8	24.3	41.3
31.25	11.7	42.9	33.9	23.6	39.9
62.5	17.0	38.4	27.8	21.5	35.4
100	22.0	35.3	23.8	20.1	32.3

HANGZHOU RISINGSUN CABLE CO.,LTD

Add:1188 Jinxi Rd.s Linglong Industrial Zone Lin'an,Zhejiang,China

Tel: 86-571-63766698 Fax:86-571-63766808

Web:www.rscable.com